



2" STATION MONITORS

Standard Features:

- Seamless carbon steel, stainless steel or brass
- Zerk fitting for lubrication
- Operates at all pressure ranges
- Low friction loss



Potter Roemer / Fire Pro® station monitors were specifically designed to meet all requirements of municipal and petrochemical applications. The balanced flow single waterway design configuration and precision machining on swivel joints reduces friction loss while improving stream and distance, and ensures ease of operation at all pressure/flow ranges. Other details, like stainless steel components and standard epoxy powder coating inside and out, protect against corrosion. Monitors are designed to consider space, performance, and ease of use.

MODEL	HEIGHT In (mm)	WIDTH In (mm)	WEIGHT Lbs (kg)	INLET In (mm)	OUTLET In (mm)	GPM In (mm)
FP2-750	22 (559)	13 (330)	45 (20)	2-1/2" FLANGE (64)	2-1/2" (64)	750 (2839)
FP2(F/M)-750	22 (559)	13 (330)	45 (20)	2-1/2" NPT (F/M) (64)	2-1/2" (64)	750 (2839)
FP3-750	28 (711)	16 (406)	52 (24)	3" FLANGE (76)	2-1/2" (64)	750 (2839)
FP3(F/M)-750	28 (711)	16 (406)	52 (24)	3" NPT (F/M) (76)	2-1/2" (64)	750 (2839)
FP4-750*	32 (813)	22 (559)	52 (24)	4" FLANGE (102)	2-1/2" (64)	750 (2839)

* ITEM IS FM APPROVED

WWW.FIREPROMONITORS.COM